

Aerosol can storage cage: 440 can capacity

APPLICATION

For the safe and secure storage of aerosol cans.

FEATURES

- Heavy duty zinc anneal steel construction
- Durable UV-stabilised powder-coated yellow finish
- High open-area perforated side panels for natural ventilation in accordance with Australian Standards
- Solid steel roof and base
- Five fixed shelves (including base)
- Pre-drilled mounting feet (bolt down plates)
- Lockable doors each fitted with two magnetic latches and a padlock lug (padlock not included)
- Manufactured in Australia to comply with Australian Standards
- Safety and warning signage in accordance with Australian Standards



SPECIFICATIONS

Product name	Aerosol can storage cabinet
Code	ASC440
Maximum storage capacity	440 aerosol cans (65mm ø x 245mm high)
Construction material	Zinc anneal steel
Surface finish	UV-stabilised polyester powder
Paint colour	High gloss yellow
Doors	2
Shelves (including base)	5
Bolt down plates	4x pre-drilled holes - 8mm ø
Shipping weight	102kg

DIMENSIONS (W x D x H)

External dimensions	1250mm x 465mm x 1720mm
Internal dimensions	1170mm x 400mm x 1700mm

MANUFACTURED TO MEET THE REQUIREMENTS OF

AS/NZS3833-2007	The storage and handling of mixed classes of dangerous goods, in packages and intermediate bulk containers
AS1319-1994	Safety signs for the occupational environment
ADG CODE 7.5	Australian Dangerous Goods Code 2017 Edition 7.5
AS4506-2005	Metal finishing - Thermoset powder coatings



Class 2: Flammable Gas

Flammable gases are gases which at 20°C and a standard pressure of 101.3 kPa:

- (i) are ignitable when in a mixture of 13 per cent or less by volume with air; or
- (ii) have a flammable range with air of at least 12 percentage points regardless of the lower flammable limit. Flammability should be determined by tests or by calculation in accordance with methods adopted by ISO (see ISO 10156:2010).

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5