Phone: 1300 903 933

Email: office@wssa.com.au

Web: www.wssa.com.au



6 Drum Bund - Low Profile Specification Sheet

6 Drum Bund - Low Profile (DBPG6LP)	
Dimensions	1820mm (L) x 1210mm (w) x 150mm(H)
Capacity	240 Litres
UDL	3,500 kg
Material (Bund)	Rota-Moulded Polyethylene
Material (Grate)	High Impact, Injection Moulded Polypropylene
Weight	45kg (with Grate) - 22kg (no Grate)







DBPG6LP: 6 Drum bund low profile polyethylene with removable grate

Application: Store 6 x 205 litre drums to capture leaks, drips and spills

- Heavy duty Australian made 'six drum' storage bund.
- Polyethylene construction provides excellent corrosion resistance to oils, fuels and a range of chemicals.
- · 240 litre integral spill containment sump.
- · Removable two piece polypropylene grated top allows easy access for cleaning.
- · Store drums directly or palletised on the bund.
- Dimensions (cm): 182 (l) x 122 (w) x 15 (h).
- Uniformly distributed load: 3500 kg.
- Weight: 45 kg.
- Load tested in Australia by NATA accredited engineers dynamic compression test certificate available.
- · Can be connected to other low profile bunds to create customised working platforms.
- Available upon request: Drum Bund Joiner Strip & Connector for assembly of bunded work platform

IMPORTANT! Before starting to create a bunded platform:

- The area where the bunded area is to be situated <u>must</u> be free from rocks, sticks, small stones, grit or debris. Sweep the area clean prior to assembly
- The area where the bunded area is to be situated must be on level ground