

Flammable liquids dangerous goods store - 160L storage capacity

APPLICATION

For the safe and secure outdoor storage of Class 3 flammable liquids and combustible liquids.

FEATURES

- Heavy duty fabricated galvanised steel construction.
- Two-coat protective finish for outdoor use.
- Rear sloping roof with gutter to allow rain water run-off.
- One adjustable shelf plus fixed base shelf.
- Single 270° opening door with ISO locking bar.
- Integral spill containment bund with externally accessible drain.
- Fitted with earth lug and supplied with an earth stake for site install if required.
- Ventilated in accordance with Australian Standards.
- Safety and warning signage applied in accordance with Australian Standards.
- Manufactured in Australia to meet the requirements of AS1940-2017 "The storage and handling of flammable and combustible liquids".



SPECIFICATIONS

Product name	Flammable liquids dangerous goods store
Code	FLC160-OD
Maximum storage capacity	160 litres
Construction material	Galvanised steel
Surface finish and colour	Epoxy powder undercoat + UV-stabilised polyester powder topcoat
Colour	Yellow
Doors	1
Shelves (including base)	2
Shipping weight	220 kg
Bund capacity	131 litres

MANUFACTURED TO MEET THE REQUIREMENTS OF

AS1940-2017	The storage and handling of flammable and combustible liquids
AS1319-1994	Safety signs for the occupational environment
ADG CODE 7.5	Australian Dangerous Goods Code 2017 Edition 7.5
AS4506-2005	Metal finishing - Thermoset powder coatings

DIMENSIONS (W x D x H)

External dimensions	1058mm x 982mm x 1380mm
Internal dimensions*	838mm x 840mm x 1080mm

* Useable internal dimensions



Class 3: Flammable Liquids

Flammable liquids are liquids, or mixtures of liquids, or liquids containing solids in solution or suspension (for example, paints, varnishes, lacquers, etc., but not including substances otherwise classified on account of their dangerous characteristics) which give off a flammable vapour at temperatures of not more than 60 °C, closed-cup test, or not more than 65.6 °C, open-cup test, normally referred to as the flash point.

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5