DANGEROUS GOODS STORAGE SPECIALISTS

Phone: 1300 903 933

Email: office@wssa.com.au

Web: www.wssa.com.au



Flammable liquids dangerous goods store - 250L storage capacity



APPLICATION

For the safe and secure outdoor storage of Class 3 flammable liquids and combustible liquids.

FEATURES

- Heavy duty fabricated galvanised steel construction.
- High-build two-pack epoxy primer and semi-gloss two-pack polyurethane yellow topcoat = total dry film build in excess of 200 microns (meets AS2312.1-2014).
- Rear sloping roof with gutter to allow rain water run-off.
- Two adjustable shelves plus fixed base shelf.
- Single 270° opening door with ISO locking bar.
- Integral spill containment bund with externally accessible drain.
- Fitted with earth lug and supplied with an earth stake for site install if required.
- Ventilated in accordance with Australian Standards.
- Safety and warning signage applied in accordance with Australian Standards.
- Manufactured in Australia to meet the requirements of AS1940-2017
 "The storage and handling of flammable and combustible liquids".



SPECIFICATIONS	
Product name	Flammable liquids dangerous goods store
Code	FLC250-OD
Maximum storage capacity	250 litres
Construction material	Galvanised steel
Surface finish and colour	High-build two-pack epoxy primer and semi- gloss two-pack polyurethane yellow topcoat
Doors	1
Shelves (including base)	3
Shipping weight	265kg

MANUFACTURED TO MEET THE REQUIREMENTS OF		
AS1940-2017	The storage and handling of flammable and combustible liquids	
AS1319-1994	Safety signs for the occupational environment	
ADG CODE 7.5	Australian Dangerous Goods Code 2017 Edition 7.5	
AS2312-2014	Guide to the protection of structural steel against atmospheric corrosion by the use of protective coatings	

DIMENSIONS (W x D x H)		
External dimensions	1060mm x 982mm x 2000mm	
Internal dimensions	838mm x 840mm x 1600mm	



Class 3: Flammable Liquids

Flammable liquids are liquids, or mixtures of liquids, or liquids containing solids in solution or suspension (for example, paints, varnishes, lacquers, etc., but not including substances otherwise classified on account of their dangerous characteristics) which give off a flammable vapour at temperatures of not more than 60 °C, closed-cup test, or not more than 65.6 °C, open-cup test, normally referred to as the flash point.

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5