DANGEROUS GOODS STORAGE SPECIALISTS

Phone: 1300 903 933

Email: office@wssa.com.au

Web: www.wssa.com.au



Flammable Liquids dangerous goods store - 4x drums / single pallet (850L)


APPLICATION

For the safe and secure outdoor storage of Class 3 flammable liquids and combustible liquids.

FEATURES

- Store up to 4x 205 litre drums individually or on a pallet
- Heavy duty fabricated galvanised steel construction
- Two-coat protective finish for outdoor use.
- · Rear sloping roof with gutter to allow rain water run-off.
- Single 270° opening door with ISO locking bar.
- Fitted with earth lug and supplied with an earth stake for site install if required.
- Ventilated in accordance with Australian Standards.
- Safety and warning signage applied in accordance with Australian Standards.
- Manufactured in Australia to meet the requirements of AS1940-2017
 "The storage and handling of flammable and combustible liquids".





SPECIFICATIONS		
Product name	Flammable liquids dangerous goods store	
Code	FLC850P-OD	
Maximum storage capacity	850 litres	
Construction material	Galvanised steel	
External surface finish	Epoxy powder undercoat + UV-stabilised polyester powder topcoat	
Colour	Yellow	
Doors	1	
Shelves (including base)	1	
Shipping weight	380kg	
Bund capacity	254 litres	

MANUFACTURED TO MEET THE REQUIREMENTS OF		
AS1940-2017	The storage and handling of flammable and combustible liquids	
AS1319-1994	Safety signs for the occupational environment	
ADG CODE 7.5	Australian Dangerous Goods Code 2017 Edition 7.5	
AS2312-2014	Guide to the protection of structural steel against atmospheric corrosion by the use of protective coatings	

DIMENSIONS (W x D x H)	
External dimensions	1546mm x 1446mm x 1700mm
Internal dimensions*	1210mm x 1200mm x 1297mm

* Useable internal dimensions



Class 3: Flammable Liquids

Flammable liquids are liquids, or mixtures of liquids, or liquids containing solids in solution or suspension (for example, paints, varnishes, lacquers, etc., but not including substances otherwise classified on account of their dangerous characteristics) which give off a flammable vapour at temperatures of not more than 60 °C, closed-cup test, or not more than 65.6 °C, open-cup test, normally referred to as the flash point.

Referenced from the Australian Dangerous Goods Code, 2017, Edition 7.5