

## Oxidising agents safety cabinet - 100L storage capacity

### APPLICATION

For the safe and secure indoor storage of Class 5, Division 5.1 oxidising agents.



### FEATURES

- Double wall construction with 40mm thermal barrier
- Vent ports with integral flash arrestors fitted on each side
- Self-closing, non-lockable door fitted with adjustable hydraulic closure
- Door releases in event of pressure build up (meets AS4326-2008, section 4.8.3)
- Adjustable hydraulic door closure
- Flush mount handle
- Continuous piano hinge on door delivers smooth closure
- One adjustable shelf plus fixed base shelf
- Internal spill containment bund with suspended perforated floor
- Durable UV stabilised thermosetting polyester powder coat finish
- Grounding connector enables earthing if required
- Adjustable screw-in feet for optional elevation
- Safety and warning signage applied in accordance with Australian Standards
- NOT TO BE USED FOR STORING AMMONIUM NITRATE



### SPECIFICATIONS

Product name	Oxidising agents safety cabinet
Code	OAC100
Maximum storage capacity	100 litres
Construction material	Steel
Surface finish	UV-stabilised polyester powder
Paint colour	Yellow
Doors	2
Shelves (including base)	2
Shipping weight	95kg

### DIMENSIONS (W x D x H)

External dimensions	1110mm x 510mm x 800mm
Internal dimensions	1010mm x 420mm x 550mm

### MANUFACTURED TO MEET THE REQUIREMENTS OF

AS4326-2008	The storage and handling of oxidising agents
AS1319-1994	Safety signs for the occupational environment
ADG CODE 7.6	Australian Dangerous Goods Code 2018 Edition 7.6
AS4506-2005	Metal finishing - Thermoset powder coatings



### Class 5.1: Oxidising Agents

Substances which, while in themselves not necessarily combustible, may, generally by yielding oxygen, cause, or contribute to, the combustion of other material. Such substances may be contained in an article.

Referenced from the Australian Dangerous Goods Code, 2018, Edition 7.6